

# LSM Model: EcoVend RVM 400 / 400-X Specification

<b>Location:</b>	Internal or external (under cover)
<b>Dimensions (mm):</b>	<b>RVM400</b> - 1900 (H) x 1250 (W) x 1050 (D) <b>RVM400-X</b> - 1900(H) x 1350(W) x 1050/1500 (D)
<b>Footprint:</b>	<b>RVM400</b> 1.31m2 <b>RVM400-X</b> 1.42m2 / 2.03m2
<b>Tare Weight:</b>	<b>RVM400</b> - 490kg <b>RVM400-X</b> 525 kg / 535kg
<b>Screens:</b>	<b>User</b> 17.3" <b>Multimedia / Advertising</b> 55"
<b>Advertising Side Light Boxes:</b>	67" x 2
<b>Reward / Deposit Return System:</b>	Digital incl Loyalty Card, Smartphone App & paper voucher
<b>Material Type:</b>	Plastic bottles (PET) and Metal cans
<b>Capacity (Subject to format – up to)</b>	1000 – 1700 PET bottles, 3000 – 5100 Metal cans
<b>Segregated:</b>	Yes
<b>Automation:</b>	Barcode, Shape, material and weight sensors
<b>Barcode:</b>	EAN
<b>Container Size:</b>	Maximum 3 Litres (uk standard sizes)
<b>Compaction:</b>	Yes
<b>Power Supply:</b>	13 amps, 3 pin, single phase
<b>Operating Voltage:</b>	220/230V AC
<b>Productivity (Up to):</b>	<b>RVM400</b> 15 units per min <b>RVM400-X</b> 45 units per min
<b>IP Rating and Interface:</b>	IP40 (under cover), LAN/WIFI/DATA SIM/ROUTER
<b>Temperature Range:</b>	-10 degrees to 40 degrees

